

**GEROtherm® UNI-FIX**

As a weight connector for universal weight attachment and the fastening of double U GEROtherm® probe feet 32–43 mm.

Max. load: 100 kg.

No mechanical safeguard

Length approx. 230 mm

Art. No.: 104606

Quantity: ..... Units

**UNI-FIX 2020**

Length approx. 245 mm

Art. No.: 113284

Quantity: ..... Units

**GEROtherm® weight connector de50mm**

As a weight connector for universal weight attachment and the fastening of double U or single U GEROtherm® probe feet 50 mm. Matching with additional weight 20 kg (104644)

Max. load: 300 kg.

Doppel-U:

Length approx. 340 mm

Art. No.: 116841

Quantity: .....Units

Single-U:

Length approx. 155 mm

Art. No.: 118139

Quantity: ..... Units

**GEROtherm® PUSH-FIX**

Impact-resistant sleeve and weight connector for the installation of GEROtherm® probe feet (32–43 mm) with linkage support.

Max. impact: 2,000 kg.

Single U 32 mm

Length approx. 370 mm

Outside diameter with deflection: approx. 94 mm

Art. No.: 108139

Quantity: ..... Units

Single U 35 mm REX

Length approx. 370 mm

Outside diameter with deflection: approx. 96 mm

Art. No.: 108140

Quantity: ..... Units

Single U 40 mm

Length approx. 385 mm

Outside diameter with deflection: approx. 112 mm

Art. No.: 108141

Quantity: ..... Units

Single U 43 mm REX  
Length approx. 385 mm  
Outside diameter with deflection: approx. 112 mm  
Art. No.: 108143  
Quantity: ..... Units

Double U 32 mm  
Length approx. 370 mm  
Outside diameter with deflection: approx. 100 mm  
Art. No.: 108144  
Quantity: ..... Units

Double U 35 mm REX  
Length approx. 370 mm  
Outside diameter with deflection: approx. 105 mm  
Art. No.: 108146  
Quantity: ..... Units

Double U 40 mm  
Length approx. 385 mm  
Outside diameter with deflection: approx. 118 mm  
Art. No.: 108147  
Quantity: ..... Units

Double U 43 mm REX  
Length approx. 385 mm  
Outside diameter with deflection: approx. 120 mm  
Art. No.: 108149  
Quantity: ..... Units

Double U 43 mm FLUX (extended version)  
Length approx. 920 mm  
Outside diameter with deflection: approx. 121 mm  
Art. No.: 118014  
Quantity: ..... Units

Double U 53 mm FLUX (extended version)  
Length approx. 1200 mm  
Outside diameter with deflection: approx. 148 mm  
Art. No.: 118201  
Quantity: ..... Units

#### **GERO<sup>®</sup>therm<sup>®</sup> INTERFACE**

for simple incorporation of the impact-resistant sleeve in combination with the GERO<sup>®</sup>therm<sup>®</sup> PUSH-FIX

Length approx. 635 mm  
Art. No.: 108157  
Quantity: ..... Units