

**GEROthern® SAVE 125 collector/distributor with flat-sealing ball valves**

GEROthern® collector/distributor made of PE 100, with a silvery surface, SDR11 / PN16 for connecting the geothermal probes and feeding to the heat pump. Weld seams made in accordance with DVS, quality monitoring in accordance with the directive HR3.26 of the Süddeutsches Kunststoffzentrum (SKZ) Würzburg/Germany. Minimal flow resistances. Specially developed for geothermal use. Flow rate **max. 19.6 m<sup>3</sup>/h @ 1 m/s**

- Main body de 125 mm
- Flat-sealing ball valves type GF375 with pipe sockets PE100-RC, SDR11 / PN16 for connection to electrofusion coupler sockets or compression fittings
- 1 ball valve type GF375 as filling/drainage valve
- 3 sockets Rp ½" IT for thermometer, bleeder and left/right usage
- Selectable outlet:
  - Pipe: PE100-RC de 110 mm / 90 mm / 75 mm / 63 mm
  - OT: R2½"; R2"
  - IT: Rp 2"
  - Loose flange: de 110 mm / 90 mm / 75 mm / 63 mm
- Delivered separately:
  - 3 sockets R½" made of PA
  - 1 bleeder R½" with large passage

Packaged and delivered in a cardboard box/on pallets

Number of connections (2–15 possible): .....

Connection dimensions (40 mm or 50 mm): .....

Selected outlet: .....

Art. No.: .....

Quantity ..... Units

**GEROthem® SAVE 125 collector/distributor with flat-sealing  
Hyline balancing valve and filling/drainage valve**

GEROthem® collector/distributor made of PE 100, with a silvery surface, SDR11 / PN16 for connecting the geothermal probes and feeding to the heat pump. Weld seams made in accordance with DVS, quality monitoring in accordance with the directive HR3.26 of the Süddeutsches Kunststoffzentrum (SKZ) Würzburg/Germany. Minimal flow resistances. Specially developed for geothermal use. Flow rate **max. 19.6 m<sup>3</sup>/h @ 1 m/s**

- Main body de 125 mm
- Flat-sealing Hyline balancing valves 20–60 l/min
- 1 ball valve made of PVC as filling/drainage valve
- 3 sockets Rp ½" IT for thermometer, bleeder and left/right usage
- Selectable outlet:
  - Pipe: PE 100 de 110 mm / 90 mm / 75 mm / 63 mm
  - OT: R2½"; R2"
  - IT: Rp 2"
  - Loose flange: de 110 mm / 90 mm / 75 mm / 63 mm
- Delivered separately:
  - Transition pieces with OT and pipe PE100-RC, SDR11 / PN16 for connection to electrofusion coupler sockets or compression fittings
  - 3 sockets R½" made of PA
  - 1 bleeder R½" with large passage

Packaged and delivered in a cardboard box/on pallets

Number of connections (2–15 possible): .....

Connection dimensions (40 mm or 50 mm): .....

Selected outlet: .....

Art. No.: .....

Quantity ..... Units

**GEROthem® SAVE 125 collector/distributor with flat-sealing inline balancing valves and filling/drainage valve**

GEROthem® collector/distributor made of PE 100, with a silvery surface, SDR11 / PN16 for connecting the geothermal probes and feeding to the heat pump. Weld seams made in accordance with DVS, quality monitoring in accordance with the directive HR3.26 of the Süddeutsches Kunststoffzentrum (SKZ) Würzburg/Germany. Minimal flow resistances. Specially developed for geothermal use. Flow rate **max. 19.6 m<sup>3</sup>/h @ 1 m/s**

- Main body de 125 mm
- Flat-sealing inline balancing valves 5–42 or 20–70 l/min
- 1 ball valve type GF375 as filling/drainage valve
- 3 sockets Rp ½" IT for thermometer, bleeder and left/right usage
- Selectable outlet:
  - Pipe: PE 100 de 110 mm / 90 mm / 75 mm / 63 mm
  - OT: R2½"; R2"
  - IT: Rp 2"
  - Loose flange: de 110 mm / 90 mm / 75 mm / 63 mm
- Delivered separately:
  - Transition pieces with OT and pipe PE 100/SDR11 for connection to electrofusion coupler sockets or compression fittings
  - 3 sockets R½" made of PA
  - 1 bleeder R½" with large passage

Packaged and delivered in a cardboard box/on pallets

Number of connections (2–15 possible): .....

Connection dimensions (40 mm or 50 mm): .....

Selected outlet: .....

Art. No.: .....

Quantity ..... Units

**Fastening set for GEROtherm® SAVE 125**

For attaching the SAVE collectors/distributors, for a pair consisting of:

- 4 standard pipe clamps, galvanised steel S248.4JRG2, temperature resistance from -48.4°C to +100°C, lock with pendulum nuts, two-part design, soundproofing for DIN 4109 including EPDM rubber sound insulation insert, building material class B2 “normally flammable” according to DIN 4102, resistant to ozone, weather and ageing
- 4 base plates with threaded connection 1/2" internal thread for mounting on the structure, mounting rails or other objects, galvanised steel S248.4JR
- 2 threaded rods 1/2" cut length 50 mm, galvanised steel (min. 8 µm), for spacing the rear distributor
- 2 threaded rods 1/2" cut length 200 mm, galvanised steel (min. 8 µm), for spacing the front distributor
- 8 strap screws incl. integrated washer de 18 mm, screw length 80 mm, head with wrench size 13 or Torx 30, galvanised steel (min. 8 µm)
- 8 DELTA plugs made of PA 6
- Delivered fully packaged in a suitable cardboard box

**For SAVE 125**

Art. No.: 104586

Quantity ..... Units