

**GERO<sup>therm</sup>® SAVE 180 collector/distributor with flat-sealing ball valves and filling/drainage valve**

GERO<sup>therm</sup>® collector/distributor made of PE 100, black, SDR11 / PN16 for connecting the geothermal probes and feeding to the heat pump. Weld seams made in accordance with DVS, minimal flow resistances. Specially developed for geothermal use. Flow rate **max. 48.4 m<sup>3</sup>/h @ 1 m/s**

- Flat-sealing ball valves type GF375 with pipe sockets PE100-RC, SDR11 / PN16 for connection to electrofusion coupler sockets or compression fittings
- 1 ball valve type GF375 as filling/drainage valve
- 3 sockets Rp ½" IT for thermometer, bleeder and left/right usage
- Selectable outlet:
  - Pipe: PE 100 de 160/125/110 mm
  - Loose flange: de 160/125/110
- Delivered separately:
  - 3 sockets R½" made of PA
  - 1 bleeder R½" with large passage

Delivered packed on pallets

Number of connections (customer specific): .....

Connection dimensions (40 mm or 50 mm): .....

Selected outlet: .....

Art. No.: .....

Quantity ..... Units

**GEROthem® SAVE 180 collector/distributor with flat-sealing  
Hyline balancing valves and filling/drainage valve**

GEROthem® collector/distributor made of PE 100, black, SDR11 / PN16 for connecting the geothermal probes and feeding to the heat pump. Weld seams made in accordance with DVS, minimal flow resistances. Specially developed for geothermal use. Flow rate **max. 48.4 m<sup>3</sup>/h @ 1 m/s**

- Flat-sealing Hyline balancing valves with pipe sockets PE100-RC, SDR11 / PN16 for connection to electrofusion coupler sockets or compression fittings
- 1 ball valve type GF375 as filling/drainage valve
- 3 sockets Rp 1/2" IT for thermometer, bleeder and left/right usage
- Selectable outlet:
  - Pipe: PE 100 de 160/125/110 mm
  - Loose flange: de 160/125/110
- Delivered separately:
  - 3 sockets R1/2" made of PA
  - 1 bleeder R1/2" with large passage
  -

Delivered packed on pallets

Number of connections (customer specific): .....

Connection dimensions (40 mm or 50 mm): .....

Selected outlet: .....

Art. No.: .....

Quantity ..... Units

**GERO<sup>therm</sup>® SAVE 180 collector/distributor with flat-sealing inline balancing valves and filling/drainage valve**

GERO<sup>therm</sup>® collector/distributor made of PE 100, black, SDR11 / PN16 for connecting the geothermal probes and feeding to the heat pump. Weld seams made in accordance with DVS, minimal flow resistances. Specially developed for geothermal use. Flow rate **max. 48.4 m<sup>3</sup>/h @ 1 m/s**

- Flat-sealing inline balancing valves with pipe sockets PE100-RC, SDR11 / PN16 for connection to electrofusion coupler sockets or compression fittings
- 1 ball valve type GF375 as filling/drainage valve
- 3 sockets Rp ½" IT for thermometer, bleeder and left/right usage
- Selectable outlet:
  - Pipe: PE 100 de 160/125/110 mm
  - Loose flange: de 160/125/110
- Delivered separately:
  - 3 sockets R½" made of PA
  - 1 bleeder R½" with large passage

Delivered packed on pallets

Number of connections (customer specific): .....

Connection dimensions (40 mm or 50 mm): .....

Selected outlet: .....

Art. No.: .....

Quantity ..... Units

**Fastening set for GEROtherm® SAVE 180**

For attaching the SAVE collectors/distributors, for a pair consisting of:

**Basic module**

- 4 pipe clamps
- 4 base plates with threaded connection 1/2" internal thread
- 4 threaded pipes 1/2" cut length 200 mm
- 8 mounting bolts
- 2 C-profile brackets 45/60 length 735 mm
- 2 end caps for C-profile bracket
- 4 bolt anchors BZ plus
- Delivered fully packaged in a suitable cardboard box
- 

**For SAVE 180**

Art. No.: 104587

Quantity ..... Units

**Extension module**

- 2 pipe clamps
- 2 base plates with threaded connection 1/2" internal thread
- 2 threaded pipes 1/2" cut length 200 mm
- 4 mounting bolts
- 1 C-profile brackets 45/60 length 735 mm
- 1 end caps for C-profile bracket
- 2 bolt anchors BZ plus
- Delivered fully packaged in a suitable cardboard box
- 

**For SAVE 180**

Art. No.: 104604

Quantity ..... Units