



DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-8501BN0454

Registration Number
Registriernummer

Field of Application
Anwendungsbereich

products of water supply
Produkte der Wasserversorgung

Owner of Certificate
Zertifikatinhaber

HakaGerodur AG
Mooswiesstr. 67, CH-9201 Gossau SG

Distributor
Vertreiber

HakaGerodur AG
Mooswiesstr. 67, CH-9201 Gossau SG

Product Category
Produktart

Installation systems and system joints (PN 10): drinking water installation system (8501)

Product description
Produktbezeichnung

drinking water installation system consisting of clamping- and compressing fittings made of metal, type M-MV and multilayer pipes PE-RT/Al/PE-RT; optional not pressed leaky

Model
Modell

HAKASAN

Test reports
Prüfberichte

Laboratory control test: RA3203.235802.24 from 26.04.2024 (SKZ)
Type testing: V142/20.2A from 18.11.2022 (IMA)
Supplement test: 320318/0.1/129878 from 29.06.2018 (SKZ)
Type testing: V149/17.5 from 13.11.2018 (IMA)

Test basis
Prüfgrundlagen

DVGW W 534-(P) (01.07.2015)
DVGW CERT ZP 8500 (23.05.2022)

Date of Expiry / File No.
Ablaufdatum / Aktenzeichen

31.05.2030 / 25-0230-WNV

70028-04-A-DE

30.04.2025 Le A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

14.07.25



DVGW CERT GmbH
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 9188-888
info@dvwg-cert.com
www.dvbw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
HAKASAN	Diameter: 14,0 x 2,00 mm	
HAKASAN	Diameter: 16,0 x 2,00 mm	
HAKASAN	Diameter: 20,0 x 2,00 mm	
HAKASAN	Diameter: 20,0 x 2,50 mm	
HAKASAN	Diameter: 25,0 x 3,00 mm	
HAKASAN	Diameter: 26,0 x 3,00 mm	
HAKASAN	Diameter: 32,0 x 3,00 mm	
HAKASAN	Diameter: 40,0 x 3,50 mm	
HAKASAN	Diameter: 50,0 x 4,00 mm	
HAKASAN	Diameter: 63,0 x 4,50 mm	

certified Components**zertifizierte Bauteile / Werkstoffe**

Registr. No. Registr.-Nr.	Component Bauteil (Produktart)	Model/Type Modell/Typ	Manufacturer Hersteller
DW-8236CL0506	PE-RT/Al/PE-RT tube, manufacturing group 1	HAKATHEN®/HAKATHEN®	HakaGerodur AG

Hints of Utilization / Remarks**Verwendungshinweise / Bemerkungen**

only to use with fittings: IPA Produktions- und Vertriebsges. m.b.H., A - 3163 Rohrbach

- compression fitting: made of metal, type: M-MV
- compression fitting: made of metal, type: M-MV, not pressed leaky, model: TH-U in the diameters: 16,0 x 2,00 mm; 20,0 x 2,00 mm; 26,0 x 3,00 mm; 32,0 x 3,00 mm; 40,0 x 3,50 mm
- compression fitting: made of metal, type: M-MV, model: TH-U2 in the diameters: 14,0 x 2,00 mm; 16,0 x 2,00 mm; 20,0 x 2,00 mm; 26,0 x 3,00 mm
- compression fitting: made of plastic, type: M-KV, model: TH-U2 in the diameters: 16,0 x 2,00 mm; 20,0 x 2,00 mm; 26,0 x 3,00 mm
- clamping fitting: made of metal, type: M-MV in the diameters: 16,0 x 2,00 mm; 20,0 x 2,00 mm; 26,0 x 3,00 mm

fitting material:

CW626N, CW725R, CC770S, CC752S or Radel R-5100 NT 15

only to use with multilayer pipes:

- PE-RT/Al/PE-RT (HAKATHEN®) in the diameters:
14,0 x 2,00 mm (Al: 0,18 mm), 16,0 x 2,00 mm (Al: 0,20 mm), 16,0 x 2,00 mm (Al: 0,40 mm),
20,0 x 2,00 mm (Al: 0,25 mm), 20,0 x 2,00 mm (Al: 0,40 mm), 25,0 x 2,50 mm (Al: 0,35 mm),
25,0 x 2,50 mm (Al: 0,50 mm), 26,0 x 3,00 mm (Al: 0,35 mm), 26,0 x 3,00 mm (Al: 0,50 mm),
32,0 x 3,00 mm (Al: 0,50 mm), 40,0 x 3,50 mm (Al: 0,50 mm), 50,0 x 4,00 mm (Al: 0,60 mm),
63,0 x 4,50 mm (Al: 0,80 mm)

The hygiene suitability for drinking water is proven with "certificate of conformity hygiene" according to in accordance with the currently valid legal basis.

DVGW
CERT